




# METROplank™

CONCEALED FIXED  
TIMBER DECKING



ARCHITECTURAL HARDWOOD DECKING, CLADDING & CEILING SYSTEMS



1800 894 400  
info@mortlock.com.au  
www.mortlock.com.au



# METROPLANK TIMBER DECKING PRICING GUIDE

---

## PRICING

Pricing in this document is a guide only, it could be lower or higher depending on the complexity of your project. Pricing in this document is provided for budgeting and design purposes, it provides the user a guide on where the pricing might be. Pricing is not to be used in tender quotes or quotes for your clients. Pricing made available to assist in selecting a product suitable to your budget.

Price excludes any custom or standard corner/ edging treatments, powder-coating trims, installation, substrate materials. Pricing only includes timber decking, fixing clips, screws, and pre-oiling. If pre-oiling is not required, please contact Mortlock Timber.

## TENDERS & PROJECT PROPOSALS

To make large scale projects and tenders easier, we are able measure from PDF drawings which are returned with a detailed BOQ and quotation for cross referencing. We also offer face to face proposal presentation where required. To allow for any extra fixing and corner components we require a full set of plans.

## QUANTITIES

Pricing in this guide is based on an area of 30-50m<sup>2</sup>, quantities outside this range would need to be priced per project for budgeting.

## TIMBER GRADE

Timber grade is minimum 2/3 select grade, maximum 1/3 standard grade, as per AS2796.2 unless noted otherwise.

## PRICING CHANGE

Mortlock Timber reserves the right to change pricing without notice.

## DELIVERY

Site delivery is available to all areas of Australia, Pricing listed in this guide allows for delivery to major capital cities in Australia but does not include delivery directly to site. Contact Mortlock Timber for site delivery pricing.

## WASTE ALLOWANCE

Please allow 10% extra material for waste allowance.



## METROPLANK DECKING PRICING

METROPLANK DECKING PRICING				RATE
85x20	METROPLANK	Concealed Fix Blackbutt Decking	Pre-Oiled	\$242 p/m2 + GST
85x20	METROPLANK	Concealed Fix Spotted Gum Decking	Pre-Oiled	\$242 p/m2 + GST
85x20	METROPLANK	Concealed Fix Jarrah Decking	Pre-Oiled	\$174 p/m2 + GST
85x20	METROPLANK	Concealed Fix Ironbark Decking	Pre-Oiled	\$242 p/m2 + GST
85x20	METROPLANK	Concealed Fix Pacific Teak Decking	Pre-Oiled	\$209 p/m2 + GST
130x20	METROPLANK	Concealed Fix Pacific Teak Decking	Pre-Oiled	POA p/m2 + GST
85x30	METROPLANK	Concealed Fix Blackbutt Decking	Pre-Oiled	POA p/m2 + GST
85x30	METROPLANK	Concealed Fix Spotted Gum Decking	Pre-Oiled	POA p/m2 + GST
85x30	METROPLANK	Concealed Fix Jarrah Decking	Pre-Oiled	POA p/m2 + GST
85x30	METROPLANK	Concealed Fix Ironbark Decking	Pre-Oiled	POA p/m2 + GST
85x30	METROPLANK	Concealed Fix Pacific Teak Decking	Pre-Oiled	POA p/m2 + GST
130x30	METROPLANK	Concealed Fix Blackbutt Decking	Pre-Oiled	POA p/m2 + GST
130x30	METROPLANK	Concealed Fix Spotted Gum Decking	Pre-Oiled	POA p/m2 + GST
130x30	METROPLANK	Concealed Fix Jarrah Decking	Pre-Oiled	POA p/m2 + GST
130x30	METROPLANK	Concealed Fix Ironbark Decking	Pre-Oiled	POA p/m2 + GST
130x30	METROPLANK	Concealed Fix Pacific Teak Decking	Pre-Oiled	POA p/m2 + GST



**Note:** Pricing above includes concealed fixing clips & screws



## THE SYSTEM

---

**Metroplank™** concealed fixed timber decking is a result of many years of testing and experience. Over the last 20 years Mortlock Timber has refined and adjusted the profile and clip design which allows for exactly the right amount of natural timber movement other systems do not match.


**Metroplank™** is built to last and has been used in both commercial high traffic areas as well as luxury residential homes in some of Australia's most high-profile suburbs.



# METROPLANK PROFILE & SIZES



## METROPLANK PROFILE & SIZES



**Metroplank™** offers both flat and domed top option. Flat top is generally used in areas not exposed to the weather, however if exposed a 85×20 or 85×30mm are recommended. Domed top was designed for maximum durability, the domed surface provides maximum water run-off keeping the timber dry and stable.



# TIMBER SPECIES



BLACKBUTT	
Pricing	\$\$\$
Sizes Available	85×20
Recommended Use	Residential Applications



SPOTTED GUM	
Pricing	\$\$
Sizes Available	85×20
Recommended Use	Residential & Commercial Applications



JARRAH	
Pricing	\$
Sizes Available	85×20, 85×30, 130×30
Recommended Use	Residential & Commercial Applications



IRONBARK	
Pricing	\$\$
Sizes Available	85×20
Recommended Use	Residential & Commercial Applications




PACIFIC TEAK	
Pricing	\$\$
Sizes Available	85×20, 130×20*
Recommended Use	Residential & Commercial Applications

## TIMBER SPECIES DATA

TIMBER SPECIES	BAL RATING	LENGTHS*	MOVEMENT**
Blackbutt	BAL 12.5, 19 & 29	Average Length 2.4m	High - 7.3%
Jarrah	BAL 12.5 & 19	Average Length 2.1m	High - 7%
Pacific Teak	BAL 12.5 & 19	Average Length 2.7m	Low - 4%
Spotted Gum	BAL 12.5, 19 & 29	Average Length 2.7m	Medium - 6.5%
Ironbark	BAL 12.5, 19 & 29	Average Length 2.7m	Medium - 6.1%

\* Lengths supplied range from 0.9-4.2m+ with 90% of boards 1.8m and above. Higher average means more longer length boards.

\*\* Stability of the timber, shrinkage across the board width.





## FINISHING

Timber can be supplied uncoated or fully pre-oiled prior to delivery. Mortlock Timber uses Clear Cutek CD50 penetrating oil which is designed for external use and can also be used for internal applications. To maintain the natural timber colour an additional two coats are to be applied on site as per manufacturer's application and maintenance instructions. Mortlock Timber can pre-oil with Cutek Colourtone, this adds extra cost and means longer lead times. Further information on Cutek oil can be found at [www.cutek.com.au](http://www.cutek.com.au).

## SPECIFICATION

### EXAMPLE SPECIFICATION

EXAMPLE SPECIFICATION	
Product Name	Metroplank Timber Decking System
Timber Species	Spotted Gum
Finish	Cutek CD50 Clear Oil
Board Size & Shape	85×20 Domed Surface
Fire Requirements	BAL 29
Contact	Mortlock Timber Group 1800 894 400 <a href="mailto:info@mortlock.com.au">info@mortlock.com.au</a> <a href="http://www.mortlock.com.au">www.mortlock.com.au</a>





## PRICING & TENDER SUBMISSION

To make large scale projects and tenders easier, we are able measure from PDF drawings which are returned with a detailed BOQ and an itemised proposal for cross referencing. Email plans or Tender invite to [info@mortlock.com.au](mailto:info@mortlock.com.au)



## IMPORTANT INFORMATION

---

### **UNEVEN WEATHERING**

Uneven weathering will be caused where timber is left stacked in the sun prior installing, even when the timber is plastic wrapped as plastic isn't completely UV resistant. The only way to resolve this is to leave the decking exposed for a few months and the uneven weathering will eventually fade. Decking installed in shady areas will not weather as much as timber in fully exposed areas.

### **MINIMUM GROUND HEIGHT**

We recommend timber decking to have a minimum 300mm ground clearance, so timber can breathe and allow moisture to escape.

### **EXPANSION ALLOWANCE**

Timber is a porous material and some movement should be expected. Metroplank is designed to have a 5mm spacing between the boards to allow for natural expansion.

### **DRAINAGE**

Enough drainage must be allowed underneath timber decking. If water is not able to drain or flow away from the timber it will expand beyond normal expectations and cup.

### **ONSITE STORAGE**

The decking should be kept in its original pack until installation. If it is repacked, it should be done the same as it was when delivered and must be stored out of the weather and at least 50mm off the ground.

### **TIMBER MOVEMENT**

Considering the effects of the harsh Australian climate, from heavy monsoonal rains to areas with extremely hot and dry summers you can only expect timber to move. If timber shrinks or expands slightly this is completely normal. Mortlock Timber cannot be held liable for timber that isn't maintained or in prolonged contact with moisture. This will cause timber to move beyond normal expectations.

### **TANNIN LEACHING**

Tannins are natural extractives present in most timbers, some more than others. Moisture permeating through the timber will bring these tannins to the surface which can cause stains on surrounding materials such as paving or rendered walls. Levels of tannin leaching will reduce over time and if staining does occur it should be scrubbed off as soon as possible using a stiff bristled broom and soapy water.



## INSTALLATION NOTES

Subframes for your decking (not supplied by Mortlock Timber) must be built to the relevant building regulations in your area. Tops of joists should have a joist flashing or painted black.

Joist to be set at 450mm centres for 20mm thick decking and 600mm centres for 30mm thick decking, Metroplank can be installed on timber or steel joists.

Decking should be secured with no less than an 8-gauge self-drilling fastener. Metroplank is available with 2 types of screws specially designed for the system, one for timber joists and the other for steel joists, please specify when requesting quotes and ordering.

To avoid cutting the last board to final width, consider building the subframe to a width to suit the incremental sequence of the boards. For example: 2400mm deck width. 85mm board with a 5mm spacing has a 90mm cover. Therefore  $2400 \div 90\text{mm} = 26.67$  boards. 27 boards x 90mm is 2430mm total width. Final width =  $90 \times 27 = 2430$ .

Use a 5mm spacer to maintain a consistent gap between the end of the decking boards and adjacent walls.





# INSTALLATION

## 01 STARTING POINT & EDGE BOARDS

If the laying direction is 90 degrees to building, start at either end of your deck.

If decking is being laid parallel to a wall or building, start from the outside edge so that you have a full board on the most visible edge, and work back towards the wall. Otherwise if you have built the sub frame to suit the width of the decking board to maintain full board across the deck, start at the edge against the wall.



## 02 DECKING

The board laying sequence starts at the edge moulding and works back to the wall to maintain a full board width on the most visible edge, otherwise build a sub frame to suit the width of the decking board to maintain full board across the deck.

Once the edge board has been secured, apply firm pressure downwards on the next board. Tap in with a rubber faced mallet to engage the board firmly with the preceding row of clips.



Pre-cutting and loose laying 5-10+ rows in advance is the most effective way of working. This allows you to oil the backs of the boards (pre-oiling will save oiling the back of the board) prior to laying and to see where to install double clips for butt joins in advance.

When laying over a large area, take some measurements every 5-6 rows of decking to check that the boards are keeping parallel to the edge moulding.

## 03 FASTENING CLIP


Once board is interlocking with clips fixed to the joists, slide fastening clip into groove on the exposed edge of the board till firm. Ensuring that the bottom of the clip is flush with the joist, hold clip in place and screw down. Screw should be in the centre of the clip and as close to 90 degrees to joist as possible. Screw will need to be on a slight angle to avoid damage the edge of the decking.





**04 BUTT JOINTING BOARDS**

Stagger the butt joints as per diagram shown. Butt joints should be centred on the joist, secured with a double clip on both sides to increase the clamping area and prevent end splitting. Joints should be staggered so the nearest joint on the same joist is 3 boards away, decking boards should span 900mm minimum for 20mm decking (connecting 3 joists at 450mm) or 1200mm for 30mm decking (connecting 3 joists at 600mm)





## MAINTENANCE



Mortlock Timber uses Cutek CD50 oil when pre-oiling. Whilst there are other products you can use, below is a recommendation for maintaining your timber decking using Cutek CD50. First coat of Cutek CD50 Clear should be applied to all surfaces of the timber prior to delivery by Mortlock Timber, with a second coat of Cutek CD50 applied once installation is complete.

Apply a second coat of Cutek CD50 with Colourtone to decking once installation is complete, to delay the silvering process and enhance the natural character and colour of the timber. Colourtone Cutek oils can still look like a clear finish, depending on the Colourtone selected. Colourtone recommendations can be found at [www.cutek.com.au/product/colourtones/](http://www.cutek.com.au/product/colourtones/)

A third coat of Cutek CD50 with Colourtone should be applied once construction is complete. A fourth coat should be applied within 6 months of third coat.

After the fourth coat, recoating time varies widely according to many factors including the age and porosity of the wood, species, situation and exposure to the weather. Typically, fully exposed decks may require coating every 1-2 years. Cutek CD50 should be reapplied when the wood is no longer beading water, or as frequently as necessary to retain the natural beauty and colour of the wood. Oil should only be applied once the previous coat has completely penetrated and is dry. The time taken for Cutek CD50 to diffuse into the timber varies significantly, depending on aspect, species, ambient temperature, porosity and moisture content of the timber.

Further information on where to buy Cutek Oil and application instructions can be found at [www.cutek.com.au](http://www.cutek.com.au)

It is not recommended that Metroplank Timber Decking is left to weather to a silver grey colour, if this look is preferred, we recommend you contact Mortlock Timber to discuss the options.



PROJECT DETAILS	
Project	Dawson Residence
Location	Coffin Bay, South Australia
Board Size	130x20
Timber Species	Pacific Teak





PROJECT DETAILS	
Project	Ewen Street Residence
Location	Perth, WA
Board Size	85x20
Timber Species	Jarrah



PROJECT DETAILS	
Project	Hillarys Residence
Location	Hillarys, WA
Board Size	130x20
Timber Species	Pacific Teak





PROJECT DETAILS	
Project	Circe Circle
Location	Hillam Architects, MAEK Residences
Board Size	85x20
Timber Species	Blackbutt



PROJECT DETAILS	
Project	Eagle Bay Residence
Location	Eagle Bay, WA
Board Size	85x20
Timber Species	Pacific Teak

## DESIGN & INSTALLATION CONSULTING

Our team can work through detailing and specification requirements to meet specific project requirements. We can assist with budget management without compromising aesthetics and ensure our products perform with an extended life cycle.

## SAMPLES

Mortlock Timber Group samples department is stocked with our full range. We use express delivery service and generally deliver samples to your door within 2-3 days. Custom samples and sample boards can take 3-6 weeks depending on requirements.



W: [www.mortlock.com.au](http://www.mortlock.com.au)

T: 1800 894 400

E: [info@mortlock.com.au](mailto:info@mortlock.com.au)

---

Distribution: WA | SA | VIC | NSW | QLD | TAS